

Redefined Your Working Space

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A (Tested at TUV SUD Singapore)
Material	1.2mm Electro Galvanize Steel
Dimension (External & Internal)	1000mm(W) x 1000mm(D) x 2280mm(H) 830mm(W) x 910mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Chamfered Edge (820mm x 320mm x 25mm)
AH Meyer NETBOX Flush 1 Power Socket & USB A + C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (2 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	1 X (11W)
Occupancy Indicator Light	YES
Air Purifying System	1 Set HEPA Filter
Heavy Duty Castor	4 PCS
Power Consumption (A)	0.18
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	266
Packing Weight (KG)	400
Wooden Crate Size	2278W x 1138D x 668H (1.74 M3)



GREENGUARD
GOLD

Lowest Total Mass Load < 0.05kg/m²
No VOCs/Phthalates/Flame Retardants



TUV
SUD

Product Certified to ISO 9001:2015
Product Certified to ISO 14001:2015
Product Certified to ISO 45001:2018

Material Selection



Global Recycled
Standard



Recycled Content

OEKO-TEX®
STANDARD 100

SPOD

3.0 Plus



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A
Material	1.2mm Electro Galvanise Steel
Dimension (External & Internal)	1250mm(W) x 1250mm(D) x 2280mm(H) 1080mm(W) x 1160mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Black Edging (1065mm x 320mm x 25mm)
AH Meyer NETBOX Flush 1 Power Socket & USB A+C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (2 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	1 X 11W
Air Purified System	1 Set HEPA Filter
Heavy Duty Castor	4 Pcs
Adjustable Foot Cap	4 Pcs
Power Consumption (A)	0.18
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	338
Packing Weight (KG)	548
Wooden Crate Size (M3)	2238W x 998D x 1396H (3.49M3)



Greenguard Gold



TUV SUD



Global Recycled Standard



OEKO-TEX Standard 100

PPOD

3.0 Plus



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A
Material	1.2mm Electro Galvanise Steel
Dimension External & Internal	1400mm(W) x 1250mm(D) 2280mm(H) 1230mm(W) x 1160mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Black Edging (1140mm x 400mm x 25mm) Sliding table
AH Meyer NETBOX Flush 1 Power Socket & USB A+C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (2 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	2 X (11W)
Air Purified System	1 Set HEPA Filter
Heavy Duty Castor	4 Pcs
Adjustable Foot Cap	4 Pcs
Power Consumption (A)	0.18
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	364
Packing Weight (KG)	574
Wooden Crate Size (M3)	2238W x 998D x 1396H (3.49M3)



Greenguard Gold Certified for Low VOC Emissions



TUV SUD

Material Selection



Global Recycled Standard



OEKO-TEX® STANDARD 100

WINPOD

3.0 Plus



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	27.6 dB According to ISO 23351-1, Speech Level Reduction, DS,A (Tested at TUV SUD Singapore)
Material	1.2mm Electro Galvanise Steel
Dimension (External & Internal)	2200mm(W) x 1250mm(D) x 2280mm(H) 2030mm(W) x 1160mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Chamfered Edging (700mm x 550mm x 25mm)
AH Meyer NETBOX Flush 1 Power Socket & USB A + C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (4 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	2 X (11W)
Air Purified System	2 Set HEPA Filter
Heavy Duty Castor	4 Pcs
Adjustable Foot Cap	6 Pcs
Power Consumption (A)	0.33
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	498
Packing Weight (KG)	673
Wooden Crate Size (M3)	2278W x 1368D x 958H (2.99 M3)



3.0 Plus

DPD



SCAN HERE

LinkedIn



Elevated Spaces

Elevated Thinking

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A
Material	1.2mm Electro Galvanise Steel
Dimension: (External & Internal)	2400mm(W) x 1600mm(D) x 2280mm(H) 2230mm(W) x 1510mm(D) x 2030mm (H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame With 9.52mm Tempered Laminated Glass
Rear Glass	8.38mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Chamfered Edging (700mm x 1050mm x 25mm)
AH Meyer NETBOX Turn 2 Power Sockets, USB A + C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (8 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	2 X (21.6W)
Air Purified System	4 Sets HEPA Filter
Heavy Duty Castor	NIL
Adjustable Foot Cap	12 PCS
Power Consumption (A)	0.47
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight	800 KG



3.0 Plus

QPOD



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A
Material	1.2mm Electro Galvanise Steel
Dimension (External & Internal)	2400mm(W) x 2400mm(D) 2280mm(H) 2230mm(W) x 2310mm(D) x 2030mm (H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Black Edging (1140mm x 400mm x 25mm) Sliding table
AH Meyer NETBOX Flush 1 Power Socket & USB A + C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	1 No x CAT 6
Ventilation Fan (12 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	2 X (29W)
Air Purified System	6 Set HEPA Filter
Heavy Duty Castor	NIL
Adjustable Foot Cap	18 Pcs
Power Consumption (A)	0.47
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	833
Packing Weight (KG)	566(A) + 543(B)
Wooden Crate Size (M3)	(A) 2378W X 1084D X 1274H (3.24M3) (B) 2378W X 1084D X 1274H (3.24M3)



CPOD

3.0 Plus



SCAN HERE

Linkedin



Redefined Your Working Space

Acoustic Properties	28.9 dB According to ISO 23351-1, Speech Level Reduction, DS,A
Material	1.2mm Electro Galvanise Steel
Dimension (External & Internal)	2400mm(W) x 3000mm(D) 2280mm(H) 2230mm(W) x 2910mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Polyester Fiber Acoustic Felt
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with 9.52mm Tempered Laminated Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Black Edging (1140mm x 400mm x 25mm) Sliding table
AH Meyer NETBOX Flush 1 Power Socket & USB A + C	Rated for 110V to 250V with a maximum of 20A. USB A + C, MAX 65W
CAT 6 LAN Outlet	NA
Ventilation Fan (12 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, Sensor Duration Adjustable
Lighting LED 4000K	2 X (40.5W)
Heavy Duty Castor	NIL
Adjustable Ball bearing	18 Pcs
Power Consumption (A)	0.47
New Interface Control Hub	Able to adjust: - Light Brightness - Fan Speed - Sensor duration - Occupancy light mode - Intermittent air circulation duration
Net Weight (KG)	833
Packing Weight (KG)	566(A) + 543(B)
Wooden Crate Size (M3)	(A) 2378W X 1084D X 1274H (3.24M3) (B) 2378W X 1084D X 1274H (3.24M3)



MPOD

3.0 Plus



SCAN HERE

Linkedin



Redefined Your Workplace

Acoustic Properties	26.3 dB According to ISO 23351-1, Speech Level Reduction, DS,A (Tested at TUV SUD Singapore)
Material	1.2mm Electro Galvanize Steel
Dimension (External & Internal)	1000mm(W) x 1000mm(D) X 2280mm(H) 830mm(W) x 910mm(D) x 2030mm(H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Acoustic Board
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminum Frame with Tempered Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Chamfered Edge (820mm x 320mm x 25mm)
AH Meyer NETBOX Flush 1 Power Socket & USB A+C	Rated for 110V to 250V with a maximum of 20A. USB A+C, MAX 30W
CAT 6 LAN Outlet	NIL
Ventilation Fan (2 Fans)	200m3/h per fan , mind 300 RPM
Motion Sensor	12V DC, 5 Mins Motion Sensor
Lighting LED 4000K	1 X (11W)
Occupancy Indicator Light	NIL
Air Purifying System	NIL
Heavy Duty Castor	NIL
Power Consumption (A)	0.18
New Interface Control Hub	NIL
Net Weight (KG)	266
Packing Weight (KG)	400
Wooden Crate Size	2278W x 1138D x 668H (1.73 M3)



3.0 Lite



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	26.3 dB According to ISO 23351-1, Speech Level Reduction, DS,A (Tested at TUV SUD Singapore)
Material	1.2mm Electro Galvanise Steel
Dimension External Internal	2200mm(W) x 1250mm(D) x 2280mm(H) 2030mm(W) x 1160mm(D) x 2030mm (H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Acoustic Board
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminium Frame With 8mm Tempered Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Chamfered Edging (700mm x 550mm x 25mm)
AH Meyer NETBOX Flush 1 Power Socket & USB + C	Rated for 110V to 250V with a maximum of 20A. USB + C, MAX 30W
CAT 6 LAN Outlet	NIL
Ventilation Fan (4 Fans)	200m3/h per fan , mind 300 RPM
Motion Sensor	12V DC, 5 Mins Motion Sensor
Lighting LED 4000K	2 X (11W)
Air Purified System	NIL
Heavy Duty Castor	NIL
Adjustable Foot Cap	6 Pcs
Power Consumption (A)	0.33
New Interface Control Hub	NIL
Net Weight (KG)	498
Packing Weight (KG)	673
Wooden Crate Size (M3)	2238W x 998D x 1396H (3.49 M3)



GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

GREENGUARD
GOLD

WIPOD

3.0 Lite



SCAN HERE

LinkedIn



Redefined Your Working Space

Acoustic Properties	Class B According to ISO 23351-1, Speech Level Reduction, DS,A (Tested at TUV SUD Singapore)
Material	1.2mm Electro Galvanise Steel
Dimension External Internal	1400mm(W) x 1250mm(D) 2280mm(H) 1230mm(W) x 1160mm(D) x 2030mm (H)
External Finishing	Epoxy Powder Coating
Internal Finishing	Acoustic Board
Floor Finishing	Fiber Nylon Carpet (Black)
Glass Door	Aluminium Frame With 8mm Tempered Glass
Rear Glass	8mm Laminated Glass
Door Closer	YES
Table	Melamine Laminated Wood With Black Edging (1140mm x 400mm x 25mm) Sliding table
AH Meyer NETBOX Flush 1 Power Socket & USB + C	Rated for 110V to 250V with a maximum of 20A. USB + C, MAX 30W
CAT 6 LAN Outlet	NIL
Ventilation Fan (2 Fans)	118 CFM Per Fan
Motion Sensor	12V DC, 5 Mins Motion Sensor
Lighting LED 4000K	2 X (11W)
Air Purified System	NIL
Heavy Duty Castor	NIL
Adjustable Foot Cap	4 Pcs
Power Consumption (A)	0.18
New Interface Control Hub	NIL
Net Weight (KG)	364
Packing Weight (KG)	574
Wooden Crate Size (M3)	2238W x 998D x 1396H (3.49M3)



WPOD

3.0 Lite



SCAN HERE

LinkedIn

